



	P/N	Cord	Length	Rating
 IEC60320-C5 IEC60884	PCR-B3EU-183B	H05VV-F 0.75mm ² 3C	1830 mm / 72 in	250V/10A
	PCR-B3EU-250B	H05VV-F 1.00mm ² 3C	2500 mm / 98.4 in	250V/10A
	PCR-RB3EU-250B	H05VV-F 1.00mm ² 3C	2500 mm / 98.4 in	250V/10A
 IEC60084 IEC60320-C13	PCR-B3REU-183B	H05VV 0.75mm ² 3C	1830 mm / 72 in	250V/10A
	PCR-B3REU-300B	H05VV 1.00mm ² 3C	3000 mm / 118 in	250V/10A
	PCR-S3REU-183B	H05VV 0.75mm ² 3C	1830 mm / 72 in	250V/2.5A
 IEC60320-C7 IEC60884	PCR-S2EU-183B	H05VVH2-F 0.75mm ² 2C	1830 mm / 72 in	250V/2.5A
 IEC60084-C14 IEC60320-C13	PCR-RB3C14-132B	H05VV-F 0.75mm ² 3C	1320 mm / 52 in	250V/10A
 IEC60320-C5 IEC60884	PCR-S3EU-183B	H05VV-F 0.75mm ² 3C	1830 mm / 72 in	250V/2.5A
	PCR-LS3EU-183B	H05VV-F 0.75mm ² 3C	1830 mm / 72 in	250V/5A