



**Sparkle Power Inc.**  
 A Leading Power Supply Manufacturer  
 Web site: [www.sparklepower.com](http://www.sparklepower.com)

## FSP200-62DL (24V)

**(RoHS Compliant)**

**200 Watts Flex DC to DC Switching Power Supply**



### Features

- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- High efficiency and reliability
- Remote ON/OFF function
- Internal 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by : UL/CUL60950-1 2<sup>nd</sup>, TUV EN60950-1 2<sup>nd</sup>, CB 60950-1 2<sup>nd</sup> , FCC, EMC

### Input Characteristics

**Input Range:** 18 ~ 36Vdc. Normal 24Vdc.

**Input Current:** 24Vdc, Max 16A

**Inrush Current:** No damage.

### Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0.0A	6A	12A	± 5%	50mV P-P
+5V	1.0A	6A	12A	± 5%	50mV P-P
+12V	1.0A	8A	16A	± 5%	120mV P-P
-12V	0.0A	0.25A	0.5A	± 10%	120mV P-P
+5Vsb	0.0A	1.0A	2.0A	± 5%	50mV P-P

\*+3.3V and +5V total output not exceed 80W

\* Total output for this subject power supply is 200W

### Specification

- **Temperature Range:** Operating: 0°C ~ +50°C; storage & shipping: -20°C ~ +80°C
- **Humidity:** 5~95% on operating & storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 2 second
- **Efficiency:** 78% minimum
- **Rise time:** Less than 20ms
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 150x81.5x40.5mm / 6x3.2x1.6inch

**Sparkle Power Inc.**  
**Main Office**  
 1000 Rock Avenue  
 San Jose, CA 95131  
 TEL: 408-519-8888  
 FAX: 408-519-9999  
 E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

**Sparkle Power Inc.**  
**Los Angeles Office**  
 17071 Green Drive  
 City of Industry, CA 91745  
 TEL: 626-839-7180  
 FAX: 626-839-3395