



**Sparkle Power Inc.**  
A Leading Power Supply Manufacturer  
Web site: [www.sparklepower.com](http://www.sparklepower.com)



## **FSP460-70PFL(SK)**

**Meet 80 PLUS Bronze, RoHS Compliant**  
**460 Watts ATX 12V Switching Power Supply**



### **Features**

- Complied with ATX12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2011/65/EU & (EU)2015/863 (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Noise Killer
- AC input I/O switch is option.
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CB 62368 & 60950-1 2<sup>nd</sup>, EMC. UL TUV, FCC

### **Input Characteristics**

**Input Range:** 90 ~ 264Vac (RMS), Full Range Input  
**Frequency:** 47 ~ 63Hz  
**Input Current:** Max 8A(RMS) @ 115Vac, 4A(RMS) @ 230Vac  
**Inrush Current:** No damage at cold start

### **Output Characteristics**

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0A	22A	± 5%	50mV P-P
+5V	0A	16A	± 5%	50mV P-P
+12V1	0.1A	18A	± 5%	120mV P-P
+12V2	0.1A	18A	± 5%	120mV P-P
-12V	0A	0.5A	± 10%	120mV P-P
+5Vsb	0.A	3.0A	± 5%	50mV P-P
-5V (option)	0.A	0.1A	± 10%	100mV P-P

- \* +3.3V and +5V total output not exceed 120W
- \* Total output for this subject power supply is 460W

### **Specification**

- **Temperature Range: Operating: 0°C ~ +50°C on full load; storage & shipping: -20°C ~ +80°C**
- **Humidity: 5~85% on operating, 5~95% on storage**
- **Dielectric Withstand: Primary frame ground 1800V AC for 2 second**
- **Efficiency: Typical > 85%**
- **Altitude: Applied for tropical Climates and use at altitudes not exceeding 5000M above sea level.**
- **Standby Power consumption (5Vsb): Efficiency> 45%@5Vsb/45mA &230Vac input (2013 Lot 6)**
- **Rise time: Less than 20ms**
- **Hold-up Time: 10 ms minimum at nominal input voltage**
- **Power Good Signal: Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)**
- **Leakage Current: Less than 3.5mA at 264Vac, 63Hz**
- **MTBF:A minimum predicted MTBF (MIL-HDBK-217) of 100,000 hours of continuous operation at +25°C.**
- **Dimensions (LxWxH): 140x150x86mm / 5.5x5.9x3.4inch**

**Sparkle Power Inc.**  
**Main Office**  
48502 Kato Road.  
Fremont CA 94538  
TEL: 408-519-8888  
FAX: 408-519-9999  
E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

**Sparkle Power Inc.**  
**Los Angeles Office**  
17071 Green Drive  
City of Industry, CA 91745  
TEL: 626-839-7180  
FAX: 626-839-3395