



Sparkle Power Inc.
A Leading Power Supply Manufacturer
Web site: www.sparklepower.com



FSP800-50WEB
(Meet 80plus Bronze, RoHs Compliant)
800 Watts 2U Switching Power Supply

Features

- Complied with 2U ATX and ATX12V standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Restriction on Hazardous Substances. Compatible with European Union Directive 2011/65/EU & (EU)2015/863, WEEE directive 2012/19/EU .
- Remote ON/OFF function
- Internal 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J, class 'B' 115Vac operation, and CISPR 22 class 'B' at 230Vac operation
- Approved by CB 62368 & 60950-1 2nd , EMC. cUL/UL TUV, FCC, CE

Input Characteristics

Input Range: 90 ~ 264Vac (RMS), Full Range Input
Frequency: 47 ~ 63Hz
Input Current: Max 12A (RMS) @ 115Vac, 6A (RMS) @ 230Vac
Inrush Current: No damage.

Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0.5A	25A	± 5%	50mV P-P
+5V	0.5A	25A	± 5%	50mV P-P
+12V	0.5A	66.5A	± 5%	120mV P-P
-12V	0.05A	0.5A	± 10%	120mV P-P
+5Vsb	0.1A	4A	± 5%	50mV P-P

*+3.3V and +5V total output not exceed 150W.
* Total output for this subject power supply is 800W

Specification

- **Temperature Range:** Operating: 0°C ~ +50°C;
storage : -20°C ~ +80°C
- **Humidity:** 5~85% RH, Non-condensing on operating,
5~95%RH, Non-condensing on storage.
- **Dielectric Withstand:** Primary frame ground 1800V AC
for 2 second
- **Efficiency:** Typical > 85%
- **Standby Power Consumption (5Vsb):**
Input Power < 1W @ 5Vsb/100mA & 230Vac input
PS_ON input signal @ High State
- **Altitude:** The power supply is applied for tropical climates
and use at altitudes not exceeding 5000m above Sea level
- **Rise time:** Less than 20ms
- **Hold-up Time:** Minimum 16ms, at 80% load.
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off
delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** A minimum predicted MTBF (MIL-HDBK-217) of
100,000 hours of continuous operation at +25°C.
- **Dimensions (LxWxH):** 240x100x70mm
9.46x3.94x2.76inch

Sparkle Power Inc.
Main Office
48502 Kato Road.
Fremont CA 94538
TEL: 408-519-8888
FAX: 408-519-9999
E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
17071 Green Drive
City of Industry, CA 91745
TEL: 626-839-7180
FAX: 626-839-3395