



**FEATURES**

- Active Power Factor Correction (PFC)
- Meet EN61000-3-2
- High efficiency and reliability
- Low noise and ripple
- Compliant with RoHS directive 2011/65/EU, WEEE directive 2002/96/EC
- Over voltage and over current protection
- Short circuit and thermal protection
- Resettable power shut down
- Internal 4cm 12Vdc fan
- 100% burn-in, Hi-pot, and ATE tested
- Meet EMI Regulatory; FCC Part 18 Subpart C, 120Vac. EN60601-1-2, EN55011, 230Vac.
- Safety approvals : UL/CUL60601, TUV 60601, CB, CE, FCC, EMC

**INPUT CHARACTERISTICS**

**Input Range:** 90 ~ 264Vac, Full Range Input

**Frequency:** 47 ~ 63Hz

**Inrush Current:** Cold start no damage

**Maximum Input Line Current:**

Model	115 Vac	230 Vac
FSP300-70MU	5A	3A

**OUTPUT CHARACTERISTICS**

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0.5A	16.0A	± 5%	50mV P-P
+5V	0.5A	18.0A	± 5%	50mV P-P
+12V1	1.0A	16.0A	± 5%	120mV P-P
+12V2	1.0A	16.0A	± 5%	120mV P-P
-12V	0A	0.5A	± 10%	150mV P-P
-5V	0A	0.2A	± 10%	120mV P-P
+5Vsb	0A	2.5A	± 5%	50mV P-P

- \* +3.3V, +5V, +12V1 and +12V2 total output shall not exceed 281W.
- \* The +3.3V and +5V total output shall not exceed 120W.
- \* Maximum combined current for 12V output shall be 20A.

**FSP300-70MU**

**300 Watts 1U ATX Medical Grade  
(80 PLUS, RoHS Compliant)**



**GENERAL SPECIFICATIONS**

- **Operating Temperature:** 0°C ~ +50°C
- **Storage Temperature:** -20°C ~ +80°C
- **Operating Humidity:** 85% RH, Non-condensing
- **Storage Humidity:** 95% RH, Non-condensing
- **Efficiency:** Typical load > 80%
- **Leakage Current:** < 0.3mA at 264Vac, 63Hz
- **Rise time:** 20ms Maximum
- **Hold-up Time:** 17 ms Minimum at 100% load
- **Dielectric Withstand:** 1800Vac for 2 second
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **MTBF:** > 100,000 hours at 100% load, 25°C
- **Dimensions:** 190mm (L) x 100mm (W) x 40.5mm (H)