



**Sparkle Power Inc.**  
 A Leading Power Supply  
 Manufacturer Website:  
[www.sparklepower.com](http://www.sparklepower.com)



**FSP250-60SNT**  
**(RoHS Compliant)**  
**250 Watts TFX Power Supply**

**Features**

- Complied with TFX12V standard
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Noise Killer (thermal fan speed control function)
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CUL/UL60950-1, TUV EN60950-1, CB 60950-1 report, FCC, EMC.

**Input Characteristics**

**Input Range:** 115Vac and 230Vac,  
**Frequency:** 47 ~ 63Hz  
**Input Current:** Max 6.5A @ 115Vac, 4A @ 230Vac  
**Inrush Current:** No damage.

**Output Characteristics**

Output	MINIMUM LOAD	NORMAL LOAD	MAXIMUM LOAD	PEAK LOAD	LOAD REG	LINE REG.	RIPPLE& NOISE
+3.3V	0.1A	9.5A	19A		±5%	±1%	70mV P-P
+5V	0.2A	7.5A	15A		±5%	±1%	70mV P-P
+12V1	0.1A	4A	8A	10A	±5%	±1%	140mV P-P
+12V2	0.5A	7A	14A	16.5A	±5%	±1%	140mV P-P
-12V	0A	0.15A	0.3A		±10%	±1%	140mV P-P
+5VSB	0A	1A	2A	2.5A	±5%	±1%	70mV P-P

**Specification**

- **Temperature Range:** Operating: +0°C ~ +25°C on full load  
 Storage & Shipping: -20°C ~ +80°C
- **Humidity:** 5-95% on operating, 5-95% on storage
- **Dielectric Withstand:** Primary to frame ground 1800V<sub>AC</sub> for 1 second
- **Rise time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 175x85x70mm / 6.9x3.4x2.8inch

\* +3.3V & +5V total output does not exceed 97W  
 \* Total output for this subject power supply is 250watts, peak load is 300W  
 \* Maximum combined current for the 12V outputs is 18A

**Sparkle Power Inc.**  
**Main Office**  
 1000 Rock Avenue  
 San Jose, CA 95131  
 TEL: 408-519-8888  
 FAX: 408-519-9999  
 E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

**Sparkle Power Inc.**  
**Los Angeles Office**  
 17071 Green Drive  
 City of Industry, CA 91745  
 TEL: 626-839-7180  
 FAX: 626-839-3395