



SPI300T8AG

(RoHS Compliant)

300 Watts TFX12V Switching Power Supply

Features

- Complied with TFX12V standard
- Active Power Factor Correction (PFC) meet EPA
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Noise Killer (thermal fan speed control function)
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CUL/UL60950-1, TUV EN60950-1 (CB Report), CE

Specification

- **Temperature Range:** Operating: 0°C ~ +40°C ; storage & shipping: -40°C ~ +70°C
- **Humidity:** 5 ~ 85% on operating, 5 ~ 95% on storage
- **Dielectric Withstand:** Primary frame ground 1800V AC for 1 second
- **Efficiency:** Up to 90%
- **Rise time:** Less than 20ms
- **Hold-up Time:** 16ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA .
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 175x85x65mm / 6.9x3.4x2.6inch

Input Characteristics

Input Range: 90 ~ 264Vac (RMS), Full Range Input

Frequency: 47 ~ 63Hz

Input Current: Max 4A (RMS) @ 115Vac, 2A (RMS) @ 230Vac

Inrush Current: No damage

Output Characteristics

	MINIMUM LOAD	NORMAL LOAD	MAXIMUM LOAD	LOAD REG.	LINE REG.	RIPPLE & NOISE
+3.3V	0.3A	9A	18A	±5%	±1%	50mV P-P
+5V	0.2A	9A	18A	±5%	±1%	50mV P-P
+12V1	0.1A	5.5A	13A	±5%	±1%	120mV P-P
+12V2	0.5A	4.0A	13A	±5%	±1%	120mV P-P
-12V	0A	0.15A	0.3A	±10%	±2%	120mV P-P
+5Vsb	0A	1.5A	3.0A	±5%	±1%	50mV P-P

*+3.3V and +5V total output not exceed 103W

* +12V1 & +12V2 total output not exceed 288W

Sparkle Power Inc.

Main Office

1000 Rock Avenue
 San Jose, CA 95131
 TEL: 408-519-8888
 FAX: 408-519-9999
 E-MAIL: info@sparklepower.com

Sparkle Power Inc.

Los Angeles Office

17071 Green Drive
 City of Industry, CA 91745
 TEL: 626-839-7180
 FAX: 626-839-3395