


## Flex Form Factor

Dimension(L\*W\*H): 190\*81.4\*40.5 (mm)



Model	Watts	+3.3V	+5V	+12V	-12V	+5Vsb	Input Voltage	Safety
FSP500-57FHB	500W	Min.	0.1A	0.1A	0.2A	0.1A	-48VDC	UL/cUL, TUV, FCC, CB, CE
		Max.	12A	12A	33A	0.3A		
(1) +3.3V&+5V total output must not exceed 90W								
FSP400-57FHB	400W	Min.	0.1A	0.1A	0.2A	0.1A	-48VDC	UL/cUL, TUV, FCC, CB, CE
		Max.	12A	12A	24.66A	0.3A		
(1) +3.3V&+5V total output must not exceed 150W								

Dimension(L\*W\*H): 150\*81.4\*40.5 (mm)



Model	Watts	+3.3V	+5V	+12V	-12V	+5Vsb	Input Voltage	Safety
FSP250-52FGB	250W	Min.	0A	0A	0.05A	0A	-24VDC	UL/cUL, TUV, FCC, CB, CE
		Max.	10A	14A	18A	0.3A		
(1) +3.3V&+5V total output must not exceed 45W								
FSP250-53FGB	250W	Min.	0A	0.2A	0.5A	0A	-48VDC	UL/cUL, FCC, CB, CE
		Max.	10A	14A	18A	0.3A		
(1) +3.3V&+5V total output must not exceed 80W								

## 1U Form Factor

Dimension(L\*W\*H): 190\*100\*40.5 (mm)



Model	Watts	+3.3V	+5V	+12V	-12V	+5Vsb	-5V	Input Voltage	Safety
FSP500-57UHB	500W	Min.	0.1A	0.1A	0.2A	0.1A	0.1A	-48VDC	UL/cUL, FCC, TUV, CB, CE
		Max.	12A	12A	33A	0.3A	2A		
(1) +3.3V&+5V total output must not exceed 90W									
FSP400-57UHB	400W	Min.	0.1A	0.1A	0.2A	0.1A	0.1A	-48VDC	UL/cUL, FCC, TUV, CB, CE
		Max.	12A	12A	24.66A	0.3A	2A		
(1) +3.3V&+5V total output must not exceed 90W									