



FSP2000-52AGPBI

**Meet 80 plus Platinum, RoHS Compliant
2000 Watts ATX 12V Switching Power Supply**



Features

- Full Modular Design.
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2011/65/EU & (EU)2015/863 (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Support Max. 16 Graphics cards (16 x PCI-E 6+2 pin)
- AC input I/O switch is included.
- Low ripple- noise.
- Output over voltage, short circuit, over current, under voltage and over temperature protection.
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CB 62368 & 60950 , EMC. CUL/UL TUV, FCC,

Input Characteristics

Input Range: 100 ~ 264Vac (RMS), Full Range Input

Frequency: 47 ~ 63Hz

Input Current: Max 15A(RMS)@ 115Vac, 12A(RMS)@ 240Vac

Inrush Current: No damage at cold start

Specification

- **Temperature Range:** Operating: 0°C ~ +50°C on full load; storage & shipping: -20°C ~ +80°C
- **Humidity:** 10~90% on operating, 95% on storage
- **Dielectric Withstand:** Primary frame ground 3000Vac for 3 second.
- **Efficiency: Typical > 92%**
- **Altitude:** Applied for tropical Climates and use at altitudes not exceeding 5000M above sea level.
- **5Vsb efficiency:** 5Vsb efficiency shall meet ENERGY STAR 5.0 and ErP requirement.
- **Rise time:** Less than 20ms
- **Hold-up Time:** 17 ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 63Hz
- **MTBF:** A minimum predicted MTBF (MIL-HDBK-217) of 100,000 hours of continuous operation at +25°C.
- **Dimensions (LxWxH):** 200x150x86mm / 7.88x5.91x3.39inch

Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Load Reg.	Ripple & Noise
+3.3V	0A	25A	± 5%	50mV P-P
+5V	0.1A	25A	± 5%	50mV P-P
+12V	0.1A	166.6A	± 5%	120mV P-P
-12V	0A	0.5A	± 10%	120mV P-P
+5Vsb	0A	4.0A	± 5%	50mV P-P

1. Maximum continuous total DC output power should not exceed 1500W at 115-200Vac.
2. Maximum continuous total DC output power should not exceed 2000W at 200-264Vac.
3. Maximum continuous combined load on +3.3VDC and +5VDC outputs shall not exceed 150W.

Sparkle Power Inc.
Main Office
48502 Kato Road.
Fremont CA 94538
TEL: 408-519-8888
FAX: 408-519-9999
E-MAIL: info@sparklepower.com

Sparkle Power Inc.
Los Angeles Office
17071 Green Drive
City of Industry, CA 91745
TEL: 626-839-7180
FAX: 626-839-3395